


SPECIFICATIONS



| | | | |
|--|---|---|---------|
| Model No. | KL15080 | | |
| Type | Series X - Fridge with castor wheels, driptray, shelves, CO2 Cylinder holder | | |
| Capacity | | | |
| Capacity | Total:Net/Gross(L) | 187L | |
| Performance | | | |
| Temperature set Range | (SN.N ST.T) | -5°C– 28°C | |
| Power | V/Hz | 115V/60hz  | |
| Compliance | MESP year | 2022 | |
| | Frost free | No | |
| | Automatic defrost | No | |
| | Adaptive defrost | No | |
| | Cyclic defrost | No | |
| | Manual defrost | Yes | |
| | Refrigerating appliance GROUP | 1 | |
| Performance | | | |
| General Features | | | |
| 1.Hidden hinge | Yes | 4.Handle | No |
| 2. Refrigerant R600A | AMOUNT: 28g | 5.Reversible Door | No |
| 3.Adjustable front legs | No | 6.Temp. control | Digital |
| Refrigerant R600A R600A is the common name for high purity isobutane (C4H10) suitable for use in the refrigeration and air conditioning industry. | Zero ozone depletion potential Very low global warming potential (<20) Excellent thermodynamic properties leading to high energy efficiency Good compatibility with components. Low charges allowing smaller heat exchangers and piping dimensions. | | |

FEATURES:

| | |
|----|---|
| 1 | Fits 4 x 19L Kegs |
| 2 | 30% Larger Evaporator |
| 3 | 25% Larger Condenser |
| 4 | 40% Thicker Side Walls for Reduced Heat Ingress. |
| 5 | 15% More Energy Efficient |
| 6 | 15% Faster Cooling |
| 7 | More Powerful and Able To More Efficiently Cool in Hotter Climates |
| 8 | Larger Compressor |
| 9 | Larger Font Fan |
| 10 | Improved Chill Plate |
| 11 | Improved Compressor |
| 12 | Improved bulkhead for twin gas line inlets. (Carb Cap Compatible KL10788) |

CDD-KLX INCLUDES:

| | |
|---|---|
| 1 | 1 x Black Plastic Wrap Around Drip Tray 30% Larger Evaporator |
| 2 | 1 x Set of 4 Castor Wheels + bolts. (2 x Front Locking, 2 Free Spinning) 40% Thicker Side Walls for Reduced Heat Ingress. |
| 3 | 1 x CO2 Cylinder Holder (designed to suit 2.6kg gas cylinder) |
| 4 | 1 x Chrome Plated Guard Rail with rubber locking feet. |

Please note: These items cannot be removed from the pack.

DIMENSIONS:

| | | |
|---|--------|--|
| 1 | Wide | 600 mm |
| 2 | Deep | 640 mm |
| 3 | Height | 840 mm (excluding castor wheels and the height of guard rail, drip tray or font) |
| 4 | Height | 890 mm of the fridge part (including cator wheels but excluding the height of guard rail, drip tray or font) |

