



SPECIFICATIONS

Additional Accessories	Beer Tower , Beer taps x 2, Keg couplers x 2,, CO2 tank x1, Misc. tools
Fridge Net Capacity	163L/5.76Cu.ft
Temperature Range	32~50 °F
Condensor	Inside
Defrost	Automatic
Foaming Components	C-P
Refrigerant	R600a
Handle	Recessed
Lock	No
Keg Size Supported	58.5L / 15.5 Gal; 30L / 7.75 Gal; 20L / 5 Gal
Temperature	Digital Display + Electronic control
CO2 Cylinder	No
Door	Stainless Steel
Interior Light	Yes
Accessories	3 shelves , guard bar, 2 casters, 2 casters with brake
CO2 Cylinder	5lbs
Weight (LBS)	95/ 112
Net Dimension	24*24*35
Packing Dimension	26*26*38

Features:

1	White powder coated steel exterior, ABS interior
2	Stainless Steel Door
3	Refrigeration system wide temperatures range
4	Chrome guard rail helps prevent glasses from sliding off
5	Plastic drip tray with rubber tips included
6	Casters included for easy moving, with lock feature casters for easy moving

7	Digital temperature control makes it easy to adjust the correct temperature for your needs
8	Automatic defrost for hassle-free maintenance
9	Uses R600a refrigerant, which is eco-friendly and more efficient
10	Refrigerator with the included wire shelving as option

MODEL	DOORS	BARRELS SUPPORTED	DIMENSIONS - W*D*H inches mm	CAPACITY cu.ft. liters	HP	AMPS	VOLTAGE	PLUG TYPE
XR-180	1	1x1/2 or 1x1/4 or 2x1/6	24*24*35 616*610*891	5.76 163	1/10-	1.2	115/60/1	NEMA 5-15P

* Height does not include 15.8"(402mm) for draft arm.

Specifications subject to change without notice.



CONFORMS TO UL STD.471,
CONFORMS TO NSF/ANSI STD.
7 CERTIFD TO CSA STD.C22.2 NO.120